

銀箭牌

工業用縫紉機

SIRUBA®



DL889 SERIES

電腦直接驅動式單針自動切線平車

Single needle direct drive lockstitch machine with thread trimmer.



適用於一般細薄至特厚布料車縫。如；襯衫、西服、牛仔布、塑膠布、皮料等之縫製
 For sewing on fine or extra heavy material, such as shirt, suit, jeans, plastic, leather..etc.

DL889

M

車縫布料
 Sewing material

L:
 薄布料 Light material

M:
 中厚布料 Medium material

H:
 厚布料 Heavy material

機種
 Model

DL889:
 電腦直接驅動式單針自動切線平車
 Single needle direct drive lockstitch machine with thread trimmer.

1

供油
 Lubrication system code

1:
 微油式
 Micro lubrication type

2:
 針棒無油式
 Semi-dry type

A

針板needle plate

— 送布牙四條齒
 4 rows of teech



A 送布牙三條齒
 3 rows of teech




3

功能碼
 Function


| 功能碼 Function | 快速倒縫 Reverse Feeding | 自動切線 Auto Thread Trimmer | 撥線桿 Wiper | 自動抬押腳 Auto Lifter |
|-----------------|-------------------------|-----------------------------|--------------|----------------------|
| 0 | ● | ● | - | - |
| 1 | ● | ● | ● | - |
| 2 | ● | ● | - | ● |
| 3 | ● | ● | ● | ● |

無油污污染，提高縫紉品質 / No Oil Stain Improve the Quality


DL889使用先進的無供油技術，不設油盤，可防止油污，提高縫紉品質。提供以下二種不同供油方式供選擇
 No oil stains, increases sewing quality. The DL889 uses advanced lubrication-free technologies, uses no oil reservoir to prevent from the oil stains, and can increase the sewing quality. The following two types of lubrication system are available :



微油式
 DL889-□1□-□
 最高縫紉速度5000rpm
 Micro lubrication type
 DL889-□1□-□
 Max. sewing speed 5000rpm




針桿無油式
 DL889-□2□-□
 最高縫紉速度5000rpm
 Semi-dry type
 DL889-□2□-□
 Max. sewing speed 5000rpm



直接驅動伺服馬達 / Direct Drive Servo Motor

DL889採用小型直接驅動伺服馬達，起縫快速、反應平順、停針定位精準。噪音低、污屑少，提高縫紉舒適度及縫紉品質。
 Direct drive mini servo motor, provides high speed start tacking and precise needle stop locating. The DL889 uses Direct drive mini servo motor system, can provide high speed start tacking, smooth reaction, and precise needle stop locating.



能耗小 / Low power consumption

能耗小，降低生產成本。DL889採用直接驅動之伺服馬達，相對於傳統皮帶驅動系統約可節省能源35%，可大幅降低生產成本。
 Low power consumption, reduces cost. The DL889 uses direct drive servo motor, provides the energy-saving upto 35% compared to traditional V-belt driven system, can reduce the production cost greatly.



良好的操作環境 / Well Operation Environment

DL889機頭操作寬度達300mm，機頭操作空間大，方便縫製物的移動。DL889以其優異的設計，大幅降低噪音與振動，提供舒適之操作環境。
 Large arm space, it makes easier for cloth handling. The DL889 owns 300mm of arm width space, it is very convenient for operation. Low noise and low vibration, it is comfortable for operation. The DL889 holds an outstanding designs, it can reduce the noise and vibration greatly and can provide the comfortable environment of operation.



獨特的壓腳設計 / Unique Design

最大壓腳提升量為16mm操作容易。且壓腳壓力調整螺絲附數字刻度，更加方便調整。
 The DL889 provides 16mm of max. lift of presser foot, it is convenient for sewing heavy materials. Presser foot tension adjusting screw with scale, it is easy for adjustment.




DL889

電腦直接驅動式單針自動切線平車
Single needle direct drive lockstitch machine with thread trimmer.

DL889-M2-3

| 機型 Model | L2 | M1 | M2 | H1 | |
|---|----------------------|--|--------------|-------------------|--------------------|
| 車縫布料 Sewing Material | 薄布料 Light | 中厚布料 Medium | 中厚布料 Medium | 厚布料 Heavy | |
|  | 4.2mm | 5mm | 5mm | 5mm | |
|  | 4000 | 5000 | 5000 | 4500 | |
| 針棒行程 Needle Bar Stroke (mm) | 29 | 31 | 31 | 35 | |
| Needle No. | NS #9~#11 | DB*1 #11~#18 | DB*1 #11~#18 | DB*1 #20~#22 | |
| 送具 Feed Dog | | · 送布牙四條齒 4 rows of teeth A · 送布牙三條齒 3 rows of teeth | | | |
|  | | · 手動提升 6mm / Hand Lift 6mm · 膝動提升 16mm / Knee Lift 16mm | | | |
| 功能碼 Function | 快速倒縫 Reverse Feeding | 自動切線 Auto Thread Trimmer | 撥線桿 Wiper | 自動抬押腳 Auto Lifter | 操作面板 Control Panel |
| 0 | ● | ● | - | - | C-60M L600A |
| 1 | ● | ● | ● | - | |
| 2 | ● | ● | - | ● | |
| 3 | ● | ● | ● | ● | |

 高林股份有限公司
KAULIN MFG. CO., LTD.



SIRUBA®

The specification and/or appearances of the equipment described in this catalogue are subject to change because of modification without previous notice.

由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知。 CAT.S60-11C SEP06